



MC 90/44 SL

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox
Fire pit: Aluker®
Firebox: Aluker®
Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 °C. Rise n'fall door, hinged opening for cleaning
Door profile: Enamelled steel
Door handle: hide away and detachable
Primary air: adjustable manually
Secondary air: adjustable manually
Tertiary air: fixed and preheated
Flue outlet: top
Fuel: wood
Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus, ducting

TECHNICAL DATA

Room heating capacity (min-max)	m ³	205 - 350
Firebox heat output	kW	15,3
Nominal thermal efficiency	%	79,3
Rated heat output	kW	12,2
Consumption at rated heat output	Kg/h	3,2
Flue outlet	Ø cm	20
Flue up to 4,5 mt	Ø cm	25
Flue over 4,5 mt	Ø cm	20
Fresh air intake (recomm. min sect.)	cm ²	200
Weight	Kg	220

On request

- Multifuoco System® ventilation kit 4 speed levels
- Multifuoco System Plus ventilation kit 4 speed levels
- Combustion air kit
- Adjustable legs kit
- Positioning handles kit

Certifications

CE conformity declaration respecting norms 89/106/CEE. Certified according to EN 13229.

The heating capacity is calculated in rooms with a requirement between 0,060 and 0,035 kW per m², depending on their insulation. Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used.



The availability of models may vary from Country to Country.

Full technical data available in pdf



MC 90/44 SL



Product Fiche



Energy Label

Compatible Cover

ESSEN - GRAZ - AMBURGO - FRIBURGO - LIPSIA - COLONIA - COLORADO - LINZ - SALISBURGO - EASY - NEW ORLEANS - CHESTER - CAMBRIDGE

TECHNICAL DRAWING

