



MA 263 B SL

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox
Firebox: in Aluker®
Fire pit: in cast iron
Hood: in steel
Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°. Rise n'fall door, hinged opening for cleaning
Door profile: in enamelled steel
Door handle: in enamelled steel
Primary air: adjustable manually
Secondary air: fixed
Flue outlet: top
Flue damper: manual
Ash pan: removable
Fuel: wood
Heating: radiant and natural convection

TECHNICAL DATA

Room heating capacity (min-max)	m ³	210-360
Nominal thermal efficiency	%	73
Rated heat output	kW	12,5
Consumption at rated heat output	Kg/h	4
Maximum heat output	kW	13,5
Maximum consumption	Kg/h	4,6
Flue outlet	Ø cm	20
Flue up to 4,5 mt	Ø cm	25
Flue over 4,5 mt	Ø cm	20
Fresh air intake (recomm. min sect.)	cm ²	300
Weight	Kg	190

ON REQUEST

- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Full technical data available in pdf



DOP MA 263 B SL



Product Fiche



Energy Label

Compatible Cover

ESSEN - GRAZ - AMBURGO - LUBECCA - FRIBURGO - LIPSIA - COLORADO - LINZ - SALISBURGO - CALAIS - EASY - NEW ORLEANS - CHESTER - CAMBRIDGE - CANBERRA - DARWIN

TECHNICAL DRAWING

