



MC 65/60

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox
Firebox: in Aluker®
Fire pit: in Aluker®
Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°. Hinged opening
Door profile: in enamelled steel
Door handle: hide away and detachable
Primary air: adjustable manually
Secondary air: adjustable manually
Tertiary air: fixed and preheated
Flue outlet: top.
Fuel: wood
Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System®

TECHNICAL DATA

Room heating capacity (min-max)	m ³	185 - 315
Nominal thermal efficiency	%	80
Rated heat output	KW	11
Consumption at rated heat output	Kg/h	3,15
Maximum heat output	KW	14,1
Maximum consumption	Kg/h	-
Flue outlet	Ø cm	18
Flue up to 4,5 mt	Ø cm	22
Flue over 4,5 mt	Ø cm	18
Fresh air intake (recomm. min sect.)	cm ²	200
Weight	Kg	155

ON REQUEST

- Multifuoco System® ventilation kit 4 speed
- Combustion air kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Full technical data available in pdf



DoP product



DoP Metal Connecting Flue Pipes



Product Fiche



Energy Label

Compatible Cover

ESSEN - VIENNA - COLONIA - BARCELONA - EASY - DARWIN - MELBOURNE

TECHNICAL DRAWING

