

Copyright c.2010. Tutti i diritti sulle immagini ed i testi sono riservati. Sono vietate la riproduzione e diffusione, anche parziale, in qualsiasi forma, delle fotografie e dei testi. I trascritti saranno perseguiti a norma di legge. Tutti i prodotti illustrati costituiscono creazione di proprietà della società Gruppo Piazzetta SpA. Ogni diritto di sfruttamento dei modelli è riservato. Il marchio ed i segni distintivi della società sono di proprietà esclusiva della stessa.



P980

Pellet stove entirely clad in majolica, with standard Multifuoco system for uniform heat from floor to ceiling, including heating to other rooms of the home by ducting a hot air flow. The standard Dual Power System with separate fan regulation, allows for managing different dedicated room temperatures. Remote management with text messages and via Wi-Fi using the app on smartphones and tablets.

COLOURS



GENERAL TECHNICAL CHARACTERISTICS

- Multifuoco System®**
Forced-ventilation system featuring 4 power levels.
Air ductable up to 16 m
- Natural Mode**
The stove continues to burn and the hot air fan switches off, heat continues to be distributed throughout the room through natural convection
- Dual Power System**
Two independent fans to obtain different temperatures in different rooms
- Management app**
Allows for managing all the stove's functions through smartphones and tablets
- Multi-functional remote control**
With LCD, timer-controlled thermostat and Multicomfort function
- Programming**
With 6 daily time frames
- Remote Control System**
Optional kit for remotely managing the stove simply through a text message
- Structure**
Steel insert with cast iron door and brazier
- Majolica cladding**
Large-size handmade pieces
- Air Glass System**
Self-cleaning ventilated ceramic glass resistant to 750°C
- Energy Saving**
Automatic switching on and off for maximum energy saving
- Wellness**
Humidifier-diffuser, also of fragrances
- Eco Function**
Automatic flame power control
- Pellet level sensor**
Allows for monitoring the amount of pellets in the tank and signals the minimum pellet level on the display and the need to refill.
- Easy Cleaning System**
Standard ash vacuum cleaner

TECHNICAL DRAWING

TECHNICAL DATA

Room heating capacity (min-max)	m ³	205-350
Rated heat output (min-max)	kW	3,5-12,2
Power adjustable (positions)		4
Nominal thermal efficiency	%	92,4
Consumption at rated heat output (min-max)	Kg/h	0,7-2,7
Dimensions WxDxH	cm	55x50x133
Cladding/front		majolica
Top		majolica
Firebox		steel
Baffle plate/Firebox/Brazier		steel / cast iron
Flue outlet Ø	cm	8
Flue direction options		-
Ash drawer		removable
Door		cast iron
Ceramic glass		resistant up to 750 °
Door handle		steel nickel plated finish
Hopper capacity	Kg	20
Umidifier in stainless steel		stainless steel
Oven in stainless steel (LxWxH)	cm	-
Multifuoco System®		standard with 4 levels of speed
Dual Power		yes
Remote control		-
Stove control panel		yes
Timer-thermostat with programming		6 daily time slots
Remote Control System		optional
Front air vents-orientable		yes
Lateral vents		-
Minimum power consumption	Watt	150
Maximum power consumption	Watt	500
Total weight	Kg	193

Calculated based on nominal heat output and refers to rooms with a thermal requirement between 0.060 and 0.035 kW per m³.

The availability of models may vary from Country to Country.

